

Transco To Go, LLC offers a range of popular sized electrodes used in the neon industry worldwide. The highest quality raw materials were chosen to offer neon manufacturers a quality product coupled with user friendly processing. The manufacturing process is closely monitored throughout and specific Q.C. procedures are incorporated to ensure consistent quality.



- ⇒ **High quality pure iron shells, nickel plated in a dedicated plant to prevent contamination.**
- ⇒ **The complete range has pure ceramic collars and mica discs.**
- ⇒ **A uniquely developed emission coating to give long life and easier processing.**
- ⇒ **Available in lead free glass.**
- ⇒ **Tubulated and non-tubulated types available.**

## TRANSCO TO GO, LLC NOVAGLO ELECTRODE SPECIFICATIONS

Transco To Go Model Number	Transco To Go Part Number	Ceramic Collar	Transco To Go Glass Specification		Transco To Go Shell Specification		Running Current M/A*
			Dia. (mm)	Length (inches)	Dia. (inches)	Length (inches)	
<b>NG1050LF</b>	TRA-1025C	✓	10	2"	1/4"	3/4"	10-25
<b>NG10T50LF</b>	TRA-1025TC	✓	10	2"	1/4"	3/4"	10-25
<b>NG1265LF</b>	TRA-1260C	✓	12	2 1/2"	5/16"	1 3/32"	25-50
<b>NG12T65LF</b>	TRA-1260TC	✓	12	2 1/2"	5/16"	1 3/32"	25-50
<b>NG13S50LF</b>	TRA-1325C 2"	✓	13	2"	5/16"	3/4"	20-30
<b>NG13ST50LF (SHORT)</b>	TRA-1325TC 2"	✓	13	2"	5/16"	3/4"	20-30
<b>NG13S57LF</b>	TRA-1325C 2.25"	✓	13	2 1/4"	5/16"	3/4"	20-30
<b>NG13ST57LF (SHORT)</b>	TRA-1325TC 2.25"	✓	13	2 1/4"	5/16"	3/4"	20-30
<b>NG13L65LF</b>	TRA-1360C	✓	13	2 1/2"	5/16"	1 3/32"	25-50
<b>NG13LT65LF (LONG)</b>	TRA-1360TC	✓	13	2 1/2"	5/16"	1 3/32"	25-50
<b>NG15S60LF</b>	TRA-1530C	✓	15	2 3/8"	3/8"	9/10"	25-38
<b>NG15ST60LF (SHORT)</b>	TRA-1530TC	✓	15	2 3/8"	3/8"	9/10"	25-38
<b>NG15L70LF</b>	TRA-1560C	✓	15	2 3/4"	3/8"	1 3/10"	50-90
<b>NG15LT70LF (LONG)</b>	TRA-1560TC	✓	15	2 3/4"	3/8"	1 3/10"	50-90

\* Running current is approximately 80% of a neon transformer's rated short circuit current.

